

FORMATI A MAGAZZINO HABA IN ACCIAIO

	K52	Planstahl	EC80	CK45	C-Stahl	Consteel	Toolox33	
Formato standard in mm	1000 x 1230	1000 x 1230	1000 x 1230	1000 x 1230	1000 x 1230	1000 x 1230	1000 x 3000	
Formato massimo in mm	2000 x 3000	2000 x 3000	2000 x 3000	2000 x 3000	2000 x 3000	1230 x 3000	2000 x 3000	
Spessore in mm	rettificato	rettificato	rettificato	rettificato	fresato	fresato	rettificato	laminato grezzo
5	○	○	○	●			○	
6	○	○	○	●			○	○
8	○	○	○	●			○	○
10	○	○	○	●	●	●	○	○
12	○	○	○	●	●	●	○	○
14				●				○
15	○	○	○	●	●	●	○	
16				●				○
17				●				
18				●				○
20	○	○	○	●	●	●	○	○
22				●				○
24								
25	○	○	○	●	●	●	○	○
27				●				
28								○
30	○	○	○	●	●	●	○	○
32				●				
35	○	○	○	●	●		○	○
36				●				
40	○	○	○	●	●	●	○	
45	○	○	○	●	●		○	○
46				●				
50	○	○	○	●	●		○	
55								○
56				●				
60	○	○	○	●	●		○	
63				●				
65								○
70	○	○	○	○	○		○	
76				○				
80	○	○	○	○	○		○	
85								○
90	○	○	○	○	○		○	
96				○				
100	○	○	○	○	○		○	
105								○
110	○	○		○	○			
120	○	○		○	○			
130	○	○		○	○			
140	○	○		○	○			
150	○	○		○	○			

- Evasione 1-3 gg
- Evasione 6-8 gg per spessori e tolleranze speciali

Su richiesta forniamo anche pezzi con spessori e tolleranze speciali
Salvo modifiche giacenze



	Toolox44		INOX V2A		INOX V4A		2316-S
Formato standard in mm	1000 x 3000		1000 x 3000		1000 x 3000		1000 x 3000
Formato massimo in mm	2000 x 3000		2000 x 3000		2000 x 3000		
Spessore in mm	rettificato	laminato grezzo	rettificato	laminato grezzo	rettificato	laminato grezzo	rettificato
5	o		o	o	o		
6	o	o	o	o	o	o	
8	o	o	o	o	o	o	o
10	o	o	o	o	o	o	o
12	o	o	o	o	o	o	o
14		o					
15	o		o	o	o	o	o
16		o	o				
17							
18		o					
20	o	o	o	o	o	o	o
22		o					
24							
25	o	o	o	o	o	o	o
27							
28		o					
30	o	o	o	o	o	o	o
32							
35	o	o	o	o	o	o	o
36							
40	o		o	o	o	o	o
45	o	o	o	o	o	o	o
46							
50	o		o	o	o	o	o
55		o					
56							
60	o		o	o	o	o	
63							
65		o					
70	o						
76							
80	o						
85		o					
90	o						
96							
100	o						
105		o					
110							
120							
130							
140							
150							

- Evasione 1-3 gg
- Evasione 6-8 gg per spessori e tolleranze speciali

Su richiesta forniamo anche pezzi con spessori e tolleranze speciali
Salvo modifiche giacenze